



## Features

- Variety of LCD Panel Size Selections
- Flat Front Panel with IP65 Design
- Solid Aluminum Die-casting Chassis
- Intel Atom N2600 processor, Dual Core Low Power Fanless System

## Specifications

System	
CPU	Intel Atom Cedar View N2600 1.6GHz Dual Core Processors
System Chipset	Intel NM10
System Memory	Onboard DDR3 2GB 800 MHz
Power Consumption	ARCHMI-710 : 11.04W ARCHMI-710P : 11.04W

IO Port	
USB	2 x USB 2.0 type A, USB4/5
Serial/Parallel	1 x RS-232/422/485 DB-9, COM1, Default RS-232 1 x RS-232 DB-9, COM2
Audio	1 x Line out phone jack
LAN	2 x GbE RJ-45
Power	3 pins terminal block connector, DC Power input

Storage Space	
HDD	1 x 2.5" SATA 2
Movable device	1 x Internal SD slot


Expansion	
On board expansion bus	1 x Mini-PCIe half size

Display	
Display Type	10.1" TFT-LCD
Max. Resolution	1280x800
Max. Color	262K
Luminance (cd/m <sup>2</sup> )	350
Viewing Angle (Degree)	160/160

Touch screen	
Type	Resistive Touch / Projected Capacitive Touch (for P model)
Interface	RS-232 / USB (for P model)
Light Transmission(%)	80% / 90% (for P model)

Power	
Power Input	9~36V DC

## Dimensions



UNIT: mm  
Tolerance: ±0.5

Mounting Hole Size

Mechanical	
Construction	Sliver aluminum front bezel and chassis
IP Rating	IP65 front panel
Mounting	Panel mounting, VESA 100 x 100
Dimensions (WxHxD)	285mm x 189mm x 48.9mm
Net Weight (Kgs)	2

Environmental	
Operating Temperature	0~50°C
Storage Temperature	-20~60°C
Storage Humidity	10 to 90% @ 40°C, non-condensing
Certificate	CE / FCC Class A

Operating System Support	
Windows XP pro	
Windows XP Embedded	
Windows Embedded CE6.0	
Windows 7 pro for Embedded	
Windows Embedded standard 7	